

# Energy Efficiency Design Summary

(Part 9 Residential)

This form to be completed & signed by the person who reviews and takes responsibility for the energy efficiency design of the project  
Information on completing this form is contained on the reverse

**For use by Principal Authority**

|                 |                            |
|-----------------|----------------------------|
| Application No: | Model/Certification Number |
|-----------------|----------------------------|

### A. Project Information

|                              |             |                                      |         |
|------------------------------|-------------|--------------------------------------|---------|
| Building number, street name |             | Unit number                          | Lot/Con |
| Municipality                 | Postal code | Reg. Plan number / other description |         |

### B. Compliance Option

|   |   |          |
|---|---|----------|
| <input type="checkbox"/> <i>SB-12 Prescriptive</i> [SB-12 - 2.1.1.] | Table:  | Package: |
| <input type="checkbox"/> <i>SB-12 Performance*</i> [SB-12 - 2.1.2.] | * Attach energy performance calculations using an approved software   |          |
| <input type="checkbox"/> <i>Energy Star®*</i> [SB-12 - 2.1.3.]      | * Attach BOP form. House must be labeled on completion by Energy Star |          |
| <input type="checkbox"/> <i>EnerGuide 80®*</i>                      | * House must be evaluated by NRCan advisor and meet a rating of 80    |          |

### C. Project Design Conditions

| Climatic Zone (SB-1):                                | Heating Equipment Efficiency              | Space Heating Fuel Source                |   |  |
|--|---|--|---|--|
| <input type="checkbox"/> Zone 1 (< 5000 degree days) | <input type="checkbox"/> ≥ 90% AFUE       | <input type="checkbox"/> Gas             | <input type="checkbox"/> Propane          | <input type="checkbox"/> Solid Fuel    |
| <input type="checkbox"/> Zone 2 (≥ 5000 degree days) | <input type="checkbox"/> ≥ 78% < 90% AFUE | <input type="checkbox"/> Oil             | <input type="checkbox"/> Electric         | <input type="checkbox"/> Earth Energy  |
| Windows+Skylights+Glass Doors                        |   | Other Building Conditions                |   |  |
| Gross Wall Area = _____ m <sup>2</sup>               | % Windows+ _____ %                        | <input type="checkbox"/> ICF Basement    | <input type="checkbox"/> Walkout Basement | <input type="checkbox"/> Log/Post&Beam |
| Gross Window+ Area = _____ m <sup>2</sup>            |   | <input type="checkbox"/> ICF Above Grade | <input type="checkbox"/> Slab-on-ground   |  |

### D. Building Specifications

| Building Component                       | RSI / R values | Building Component   | Efficiency Ratings |
|--|----------------|--|--------------------|
| <b>Thermal Insulation</b>                |                | <b>Windows &amp; Doors<sup>1</sup></b>   |                    |
| Ceiling with Attic Space                 |                | Windows/Sliding Glass Doors  |                    |
| Ceiling without Attic Space              |                | Skylights  |                    |
| Exposed Floor                            |                | <b>Mechanicals</b>   |                    |
| Walls Above Grade                        |                | Space Heating Equip. <sup>2</sup>  |                    |
| Basement Walls                           |                | HRV Efficiency (%)   |                    |
| Slab (all >600mm below grade)            |                | DHW Heater (EF)  |                    |
| Slab (edge only ≤600mm below grade)      |                | NOTES<br>1. Provide U-Value in W/m2.K, or ER rating<br>2. Provide AFUE or indicate if condensing type combined system used |                    |
| Slab (all ≤600mm below grade, or heated) |                |  |                    |

### E. Performance Design Verification [complete applicable sections if *SB-12 Performance*, *Energy Star* or *EnerGuide80* options used]

**SB-12 Performance:**  
 The annual energy consumption using Subsection 2.1.1. SB-12 Package \_\_\_\_\_ is \_\_\_\_\_ Gj (1 Gj =1000Mj)  
 The annual energy consumption of this house as designed is \_\_\_\_\_ Gj  
 The software used to simulate the annual energy use of the building is: \_\_\_\_\_  
 The building is being designed using an air leakage of \_\_\_\_\_ air changes per hour @50Pa.

**Energy Star:** BOP form attached. The house will be labeled on completion by:

**Energy Star and EnerGuide80:**  
 Evaluator/Advisor/Rater Name: \_\_\_\_\_ Evaluator/Advisor/Rater Licence #: \_\_\_\_\_

### F. Declaration [by the person who reviews and takes responsibility for the energy efficiency design]

I certify that I have reviewed the design documents submitted with the permit application, that the information contained on this form is consistent with the design documents, and that information used in any annual energy use calculations, if applicable, is a true representation of the design documents.

|      |           |       |
|------|-----------|-------|
| Name | Signature | Date: |
|------|-----------|-------|

# Guide to the Energy Efficiency Design Summary Form

The *Energy Efficiency Design Summary* form summarizes the compliance path used by a house designer to comply with energy efficiency requirements of the Ontario Building Code. This form is completed by the person responsible for the energy efficiency design of the project, and must be submitted with the building permit application. The information on this form MUST reflect the drawings and specifications being submitted, or the building permit will be refused. Refer to Supplementary Standard SB-12 for details about building code compliance requirements. Further information about energy efficiency requirements for new buildings is available from the provincial building code website at [www.mah.gov.on.ca](http://www.mah.gov.on.ca), or the municipal building department.

Beginning January 1, 2012, a house designer must use one of four energy efficiency compliance options in the building code:

1. Comply with the *SB-12 Prescriptive* design tables,
2. Use the *SB-12 Performance* compliance method, and model the design against the prescriptive standards,
3. Design to *Energy Star* standards, or
4. Evaluate the design according to *EnerGuide* technical procedures and achieve a rating of 80 or more.

## COMPLETING THE FORM

### B. Compliance Options

Indicate the compliance option being used.

- *SB-12 Prescriptive* requires that the building conforms to a package of thermal insulation, window and mechanical system efficiency requirements set out in Subsection 2.1.1. of SB-12. Energy efficiency design modeling and testing of the building is not required under this option.
- *SB-12 Performance* refers to the alternative method of compliance set out in Subsection 2.1.2. of SB-12. Using this approach the designer must use recognized energy simulation software (HOT2000 V9.34c1.2 or newer), and submit documents which show that the annual energy use of the building is equal to a prescriptive package.
- *Energy Star* houses must be designed to *Energy Star* requirements and be labelled on completion by Enerquality or other agency. The *Energy Star* BOP form must be submitted with the permit documents.
- *EnerGuide80* houses are validated by NRCan authorized energy advisors and must achieve a rating of 80 or more when evaluated in accordance with *EnerGuide* administrative and technical procedures.

### C. Project Design Conditions

*Climatic Zone:* The number of degree days for Ontario cities is contained in Supplementary Standard SB-1

*Windows, Skylights and Glass Doors:* If the ratio of the total gross area of windows, sidelights, skylights and glass doors to the total gross area of walls is more than 17%, higher efficiency glazing is required. If the ratio is more than 22% the *SB-12 Prescriptive* option may not be used. The total area is the sum of all the structural rough openings. Some exceptions apply. Refer to 2.1.1.1. of SB-12 for further details.

*Fuel Source and Heating Equipment Efficiency:* The fuel source and efficiency of the proposed heating equipment must be specified in order to determine which *SB-12 Prescriptive* compliance package table applies.

*Other Building Conditions:* These construction conditions affect *SB-12 Prescriptive* compliance requirements.

### D. Building Specifications

*Thermal Insulation:* Indicate the RSI or R-value being proposed where they apply to the house design. Under the *SB-12 Prescriptive* option, RSI 3.52 wall insulation is permitted in certain conditions where other design elements meet higher standards. Refer to SB-12 for further details.

### E. Performance Design Summary

This section is not required to be completed if the *SB-12 Prescriptive* option is being used.

## AIRTIGHTNESS REQUIREMENTS FOR NEW HOUSES

All houses must comply with increased air barrier requirements in the building code. Notice of air barrier completion must be provided and an inspection conducted prior to it being covered. A blower door test to verify the air tightness of the house must be conducted during construction if the *NRCan EnerGuide80* option is used, or if the *SB-12 Performance* or *Energy Star* options are used and an air tightness of less than 2.5 ACH @ 50 Pa in the case of detached houses, or 3.0 ACH @ 50 Pa in the case of attached houses is necessary to meet the required energy efficiency standard.

## ENERGY EFFICIENCY LABELING FOR NEW HOUSES

*Energy Star* and *EnerGuide* issue labels for new homes constructed under their energy efficiency programs. The building code does not regulate new home labelling.